

**S-FLEX SHAFT COUPLINGS  
LOVEJOY BRAND  
W.W. GRAINGERS - SUPPLIER.**

THESE ARE THE COMPONENTS REQUIRED TO COUPLE A 1/2" OR 3/4" DRILL MOTOR TO THE END OF THE EURODRIVE MOTORS USED ON MEGADOORS.


**BASIC COMPONENTS REQUIRED:**

**PARTS FROM W.W. GRAINGERS**

QTY	PART #	BODY STYLE	BORE SIZE	DESCRIPTION
TWO	1L792	4J	1/2"	S FLEX COUPLING
ONE	1L793	4J	5/8"	S FLEX COUPLING
ONE	1L794	4J	3/4"	S FLEX COUPLING
TWO	1L791	JES	N/A	JES INSERT

**PARTS FROM A MISC. HARDWARE STORE**

ONE CLEVIS PIN - 1/2" DIAMETER X 2" (MINIMUM) LONG



THE SHAFT OF THE EURODRIVE MOTOR IS DIFFERENT FOR EACH HORSEPOWER, REQUIRING MULTIPLE COUPLINGS. SHAFTS ON THE MOTORS ARE METRIC, AND THE COUPLINGS ARE SAE, SO IT IS NOT A PERFECT FIT.

CARE MUST BE TAKEN WHEN HOISTING WITH THESE COUPLINGS, TO MAKE SURE THE DOOR DOES NOT GO INTO A FREE FALL SITUATION WHEN THE BRAKE IS HELD. HOLD THE BRAKE MANUALLY. REMEMBER : WHEN YOU HAVE THE BRAKE RELEASED, AND NO TORQUE ON THE COUPLING, THE DOOR WANTS TO CLOSE.